	Cas	e 8:11-cv-01684-CJC-AN Document 1 F	Filed 11/03/11 Page 1 of 28 Page ID #:1			
Russ, August & Kabat	1 2 3 4 5 6 7 8		CLERK U.S. DISTRICT COURT SAHTA ANA ES DISTRICT COURT RICT OF CALIFORNIA			
	10	SOUTHERN DIVISION				
	11					
	12	PROXYCONN, INC.,	Case No. SACV11-01684 CJC (ANx)			
	13	Plaintiff	COMPLAINT FOR PATENT INFRINGEMENT			
3US	14	vs.	III MINGENIEM			
AU	15	ACER AMERICA CORPORATION,	JURY TRIAL DEMANDED			
USS,	16	Defendant.				
8	17					
	18					
	19					
	20					
	21					
	22					
	23					
	24					
	25					
	26					
	27					
	28					

COMPLAINT

Plaintiff Proxyconn, Inc. ("Proxyconn") alleges as follows:

PARTIES

- 1. Plaintiff Proxyconn is a California corporation with its principal place of business located at 3211 S. Shannon Street, Santa Ana, California 92704.
- 2. Defendant Acer America Corporation ("Acer") is a California corporation with its principal place of business at 333 West San Carlos Street, Suite 1500, San Jose, California 95110. Acer has appointed C T Corporation System, 818 West 7th Sreet, Los Angeles, California 90017, as its agent for service of process.

JURISDICTION AND VENUE

- 3. This action arises under the patent laws of the United States, Title 35 of the United States Code. Accordingly, this Court has subject matter jurisdiction under 28 U.S.C. §§ 1331 and 1338(a).
- 4. Venue is proper in this District under 28 U.S.C. §§ 1391 (b)-(d) and 1400(b) because Acer is subject to personal jurisdiction in this District, has committed acts of patent infringement in this District, or has a regular and established place of business in this District.

FACTUAL BACKGROUND

- 5. Proxyconn was founded in 2001 in Santa Ana, California. It remains based in Santa Ana today.
- 6. Proxyconn was started to address the problem of demands of users of networks, such as the Internet, to instantly receive content over the network. While other solutions simply relied on increasing available bandwidth, Proxyconn sought a more intelligent solution that could be used with existing technology and bandwidth.
- 7. As a result, Proxyconn created a technology that used existing technological limitations while making the use of networks effectively many times faster than previously possible. Proxyconn filed a patent application on its novel

technology. As a result of that patent application, Proxyconn was awarded United States Patent No. 6,757,717 ("the '717 patent").

8. Proxyconn's technology was used by hundreds of ISPs and hundreds of thousands of users in the US and throughout the world, and is still being used.

COUNT I

(Infringement of U.S. Patent No. 6,757,717)

- 9. Proxyconn is the owner by assignment of the '717 patent. The '717 patent is entitled "System and Method for Data Access." The '717 patent issued on June 29, 2004. A true and correct copy of the '717 patent is attached hereto as Exhibit A.
- and 22 of the '717 patent, literally and under the doctrine of equivalents, by making, using, selling, offering to sell, or importing, without license or authority, computer systems that include a sender computer and a receiver computer communicating through a network, with each computer equipped with a method for creating digital digests on data and the receiving computer including a means for comparing digital digests. In particular, these computer systems contain software including, but not limited to, the Remote Differential Compression ("RDC") technology used in at least Microsoft Corporation's Windows Server 2003 R2, Windows Server 2008, Windows Small Business Server 2003, Windows Small Business Server 2011, Windows XP with Service Pack 3, Windows Vista, and Windows 7 operating systems.
- 11. Acer has also been and still is indirectly infringing by way of inducing infringement by others or contributing to the infringement by others of the '717 patent by, among other things, making, using, importing, offering for sale, and/or selling, without license or authority, personal computers and servers for use in systems that thereby fall within the scope of at least claim 1, 10, 11 and 22 of the '717 patent. Such personal computers and servers include a sender computer and a

18

19

20

21

22

23

24

25

26

27

28

1

2

3

4

5

6

7

receiver computer communicating through a network, with each computer equipped with a method for creating digital digests on data and the receiving computer including a means for comparing digital digests. In particular, these computer systems contain software including, but not limited to, the Remote Differential Compression ("RDC") technology used in at least Microsoft Corporation's Windows Server 2003 R2, Windows Server 2008, Windows Small Business Server 2003, Windows Small Business Server 2008, Windows Small Business Server 2011, Windows XP with Service Pack 3, Windows Vista, and Windows 7 operating systems. By making, using, importing, offering for sale, and/or selling such personal computers and servers, Acer has injured Proxyconn and is thus liable to Proxyconn for infringement of the '717 patent under 35 U.S.C. § 271. Those whom Acer induces to infringe and/or whose infringement to which Acer contributes are the customers and end users of the above-referenced personal computers and servers. Acer has had knowledge of the '717 patent at least as early as the filing of this complaint and is thus liable for infringement of one or more claims of the '717 patent by actively inducing infringement and/or is liable as a contributory infringer of one or more claims of the '717 patent under 35 U.S.C. § 271.

- 12. To the extent that facts learned in discovery show that Acer's infringement of the '717 patent is or has been willful, Proxyconn reserves the right to request such a finding at time of trial.
- 13. As a result of Acer's infringement of the '717 patent, Proxyconn has suffered monetary damages in an amount adequate to compensate for Acer's infringement, but in no event less than a reasonable royalty for the use made of the invention by Acer, together with interest and costs as fixed by the Court, and Proxyconn will continue to suffer damages in the future unless Acer's infringing activities are enjoined by this Court.

14. Unless a permanent injunction is issued enjoining Acer and its agents, servants, employees, representatives, affiliates, and all others acting or in active concert therewith from infringing the '717 patent, Proxyconn will be greatly and irreparably harmed.

PRAYER FOR RELIEF

Proxyconn prays for the following relief:

- 1. A judgment that Acer has directly infringed (either literally or under the doctrine of equivalents) one or more claims of the '717 patent;
- 2. A judgment that Acer has indirectly infringed (either literally or under the doctrine of equivalents) one or more claims of the '717 patent;
- 3. A permanent injunction enjoining Acer and its officers, directors, agents, servants, affiliates, employees, divisions, branches, subsidiaries, parents, and all others acting in active concert or participation with them, from infringing the '717 patent;
- 4. An award of damages resulting from Acer's acts of infringement in accordance with 35 U.S.C. § 284;
- 5. A judgment and order requiring Acer to provide an accounting and to pay supplemental damages to Proxyconn, including, without limitation, prejudgment and post-judgment interest; and
- 6. Any and all other relief to which Proxyconn may show itself to be entitled.

JURY TRIAL DEMANDED

Proxyconn hereby demands a trial by jury of all issues so triable.

Dated: November 2, 2011 Respectfully submitted,

RUSS AUGUST & KABAT

By: Marc A. Fenster

Marc A. Fenster, Cal. Bar No. 181067

Email: mfenster@raklaw.com

Bruce D. Kuyper, Cal. Bar No. 144969
Email: bkuyper@raklaw.com
Andrew D. Weiss, Cal. Bar No. 232974
Email: aweiss@raklaw.com
12424 Wilshire Boulevard, 12th Floor
Los Angeles, California 90025
Telephone: (310) 826-7474
Facsimile: (310) 826-6991

Attorneys for Plaintiff PROXYCONN, INC.

(12) United States Patent Goldstein

(10) Patent No.: U

US 6,757,717 B1

(45) Date of Patent:

Jun. 29, 2004

(54) SYSTEM AND METHOD FOR DATA ACCESS

(75) Inventor: Leonid Goldstein, Herzlia (IL)

(73) Assignee: ProxyConn, Inc., Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/398,007

(22) Filed: Sep. 16, 1999

(56) References Cited

U.S. PATENT DOCUMENTS

4,897,781 A		1/1990	Chang et al.
5,384,565 A		1/1995	Gregory
5,682,514 A	٠	10/1997	Yohe et al 707/1
5,732,265 A		3/1998	Dewitt et al.
5,835,943 A		11/1998	Yohe et al.
5,852,717 A		12/1998	Bhide et al.
5,864,837 A		1/1999	Maimone
5,878,213 A	*	3/1999	Bittinger et al 707/10
5,909,569 A	*	6/1999	Housel et al 707/10
5,919,247 A	æ	7/1999	Van Hoff et al 709/217
5,924,116 A		7/1999	Aggarwal et al.
5,931,947 A	*	8/1999	Burns et al 713/201
5,978,791 A		11/1999	Farber et al.
6,003,087 A	*	12/1999	Housel et al 707/203
6,006,034 A		12/1999	Heath et al.
6,012,085 A		1/2000	Yohe et al.
6,021,491 A	*	2/2000	Renaud 713/179
6,073,173 A	٠	6/2000	Bittinger et al 707/513
6,085,249 A	*	7/2000	Wang et al 709/229
6,101,543 A	*	8/2000	Alden et al 709/229
6,122,637 A	*	9/2000	Yohe et al 709/204
6,134,583 A	*	10/2000	Herriot 709/217
6,148,340 A	*	11/2000	Bittinger et al 709/203
6,256,664 B1	+	7/2001	Donoho et al 709/204

OTHER PUBLICATIONS

RFC2068: Hypertext Transfer Protocol—HTTP/1.1, Jan. 1997, pp. 9-12, 29-35, 70-94, 101-138.

RFC791: Internet Protocol Darpa Internet Program Protocol

Specification, Sep. 1981, pp. 3, 11-14, 26.

RFC761: DOD Standard Transmission Control Protocol,

Jan. 1980, pp.4, 15-17.

RFC1826: IP Authentication Header, Aug. 1995, pp. 1-10. RFC1864: The Content-MD5 Header Field, Oct. 1995,

pp.1–2.

RFC1321: The MD5 Message-Digest Algorithm, Apr. 1992, pp. 1-21.

Dave Fogle, Ethernet Frame Types, article from Feb. 1996 issue of LAN Magazine/Network Magazine, pp. 1-4. W. Richard Stevens, TCP/IP Illustrated, vol. 1, 1994, pp. 33-37, 143-147, 223-228.


* cited by examiner

Primary Examiner—Jack B. Harvey
Assistant Examiner—Hai V. Nguyen
(74) Attorney, Agent, or Firm—J. D. Harriman, II, Esq.;
Coudert Brothers LLP

(57) ABSTRACT

The invention provides a system for data access in a packet-switched network, including a sender/computer including an operating unit, a first memory, a permanent storage memory and a processor and a remote receiver/computer including an operating unit, a first memory, a permanent storage memory and a processor, the sender/computer and the receiver/computer communicating through the network; the sender/computer further including device for calculating digital digests on data; the receiver/computer further including a network cache memory and device for calculating digital digests on data in the network cache memory; and the receiver/computer and/or the sender/computer including device for comparison between digital digests. The invention also provides a method and apparatus for increased data access in a packet-switched network.

34 Claims, 9 Drawing Sheets






Jun. 29, 2004

Sheet 1 of 9

US 6,757,717 B1



Client (Receiver)

Cache

Cache

Client (Sender)


Cache

C


FIG. 2 (PRIOR ART)

Jun. 29, 2004

Sheet 2 of 9



U.S. Patent Jun. 29, 2004 Sheet 3 of 9 US 6,757,717 B1







FIG. 5


U.S. Patent

Jun. 29, 2004

Sheet 4 of 9

US 6,757,717 B1





Jun. 29, 2004

Sheet 5 of 9




FIG. 8

Jun. 29, 2004

Sheet 6 of 9






FIG. 9

Jun. 29, 2004


Sheet 7 of 9






Jun. 29, 2004


Sheet 8 of 9



Jun. 29, 2004

Sheet 9 of 9





US 6,757,717 B1

1

SYSTEM AND METHOD FOR DATA ACCESS

RELATED APPLICATION

This application claims priority and is entitled to the filing date of Israeli application Ser. No. 126292 filed Sep. 18, 1998, and entitled "System And Method For Data Access," and which describes the same invention as defined herein.

FIELD OF THE INVENTION

The present invention relates to data access in networks. Specifically, the invention is concerned with a method, system and apparatus for increasing the speed of data accessing in communication networks.

BACKGROUND OF THE INVENTION

Many known applications and protocols provide means for caching and verifying of data transmitted via a network 2 (FIG. 1, prior art). Thus, a client (receiver) 4 caches data received from network 2 in cache 6. Then, when data from a remote server (sender) 8 is requested, it first searches its local cache. If the requested data is available in the cache and is verified to be valid, the client uses it, and transmission over the network is not required. Gateway or proxy caches 10 (FIG. 2, prior art) are able to operate in a similar manner.

The most well-known techniques are as follows:

1) In response to a request from a receiver, a sender attaches to the sent data an expiration time in absolute or relative form. The receiver, and possibly proxies, cache the data together with its request until the expiration time. Then the data is retrieved from the cache. In some cases, the receiver guesses the expiration time.

The problem associated with this technique is that the data entity can be changed before the expiration time, and the receiver would use an obsolete version of the data without even knowing it. Also, when the time has expired, the data will be resent, even if it is up to date.

2) In response to a request from a receiver, the sender attaches a validator to the sent data. The validator changes at least every time the data changes; in many cases, system time is used as the validator. The receiver, and possibly proxies, cache the data together with its request. When making the next request for the same data to the same sender, the receiver includes the validator. The sender keeps track of the data and resends it only if it were changed.

The problems associated with this technique are:

- a) Data is cached according to requests and senders. If the same request is directed to different servers, cached data cannot be reused.
- b) Requests without concrete data cannot be cached.
- c) The sender must track the cached data, which is not always possible.

None of the prior art techniques discussed above provides means for transmitting minor differences in data. Additionally, if data is retrieved through a caching proxy, there is a danger that an unauthorized user will have access to the data.

It is therefore a broad object of the present invention to provide a method, system and apparatus for increasing the speed of data access in a packet-switched network.

Another object of the present invention is to decrease data traffic throughout the network.

Still another object of the present invention is to decrease the required cache size.

2

A yet further object of the present invention is to maintain accessed data integrity and to improve security.

SUMMARY OF THE INVENTION

The terms "data" or "data object" as used herein refer to a file or range of octets in a file, a range of frames in a video stream or RAM-based range of octets, a transport level network packet, or the like,

The term "digital digest" as used herein refers to a fixed-size binary value calculated from arbitrary-size binary data in such a way that it depends only on the contents of the data and the low probability that two different data or objects have the same digital digest.

The term "gateway" as used herein also includes network proxies and routers.

If a sender/computer in a network is required to send data to another receiver/computer, and the receiver/computer has data with the same digital digest as that of the data to be sent, it can be assumed with sufficient probability for most practical applications that the receiver/computer has data which is exactly the same as the data to be sent. Then, the receiver/computer can use the data immediately without its actual transfer through the network. In the present invention, this idea is used in a variety of ways.

In one embodiment of the invention, a sender/computer required to send data to a receiver/computer computer initially sends a digital digest of the data. If the receiver/computer already has data with the same digital digest, it uses this data as if it were actually transmitted from the sender/computer. Additionally, digital digests for other data objects can be sent together with the principal digest. If the receiver/computer cannot find data having the principal digest, it searches for data with one of these auxiliary digests. If such data is found, the sender/computer is required to send only the difference between the requested data object and the data object corresponding to the digest.

The expression "difference between a first data or data object and a second data or data object" as used herein means any bit sequence that enables the restoration of the first data, given the second data, the bit sequence and the method employed in calculating the difference.

The invention may be implemented in a gateway system. Such a system comprises a gateway computer connected to a packet-switched network in such a way that network packets sent between at least two other computers pass through it; a caching computer connected to the gateway computer, the caching computer having a network cache memory in its permanent storage memory, means for culating a digital digest on the data it stores and means for comparison between a digital digest calculated on data in its network cache memory and a digital digest received from the packet-switched network by the gateway computer. When this system intercepts an indication signal other than a positive indication signal for a certain digital digest from a receiver/computer computer, if it has data with the same digest, it sends this data to the receiver/computer.

In another embodiment of the present invention, a client computer sends to a server computer a request including digital digests. A sender/computer forming a response then searches for data with the same digital digests as those received. If the digest of the data in the response equals one of the received digests, the server only sends confirmation. If the digest of another data is identical to one of the received digests, only the difference(s) between these data is sent.

In accordance with the present invention, there is therefore provided a system for data access in a packet-switched

network, comprising a sender/computer including an operating unit, a first memory, a permanent storage memory and a processor and a remote receiver/computer including an operating unit, a first memory, a permanent storage memory and a processor, said sender/computer and said receiver/ computer communicating through said network; said sender/ computer further including means for calculating digital digests on data; said receiver/computer further including a network cache memory and means for calculating digital digests on data in said network cache memory; and said receiver/computer and/or said sender/computer including means for comparison between digital digests.

The invention also provides a system for data access in a packet-switched network, comprising a gateway computer including an operating unit, a memory and a processor connected to said packet-switched network in such a way that network packets sent between at least two other computers pass through it; a caching computer including an operating unit, a first memory, a permanent storage memory and a processor connected to said gateway computer through a fast local network; said caching computer further including 20 a network cache memory in its permanent storage memory, means for calculating a digital digest on data stored therein and means for comparison between a digital digest calculated on data in its network cache memory and a digital digest received from said packet-switched network through 25 said gateway computer.

In addition, the invention provides a system for data access in a packet-switched network, comprising a sender/ computer including an operating unit, a first memory, a permanent storage memory and a processor and a remote 30 receiver/computer including an operating unit, a first memory, a permanent storage memory and a processor, said sender/computer and said receiver/computer communicating through a network; said sender/computer further including means for calculating digital digests on data, and said 35 receiver/computer further including a network cache memory, means for storing a digital digest received from said network in its permanent storage memory and means for comparison between digital digests.

sender/computer in a packet-switched network for increasing data access, said sender/computer including an operating unit, a first memory, a permanent storage memory and a processor and said sender/computer being operative to transmit data to a receiver/computer, the method comprising the 45 steps of transmitting a digital digest of said data from said sender/computer to said receiver/computer; receiving a response signal from said receiver/computer at said sender/ computer, said response signal containing a positive, partial negative indication signal is received, transmitting said data from said sender/computer to said receiver/computer.

The invention still further provides a method for increasing data access performed by a sender/computer in a packetswitched network, said sender/computer including an oper- 55 ating unit, a first memory, a permanent storage memory and a processor and said sender/computer being operative to transmit principal data to a receiver/computer, said method comprising the steps of transmitting digital digests of said principal data and of one or more auxiliary data from said 60 sender/computer to said receiver/computer; receiving a response signal at said sender/computer from said receiver/ computer, said response signal containing a positive, negative or partial indication signal, and if a partial indication nal constituting the difference between said principal data and corresponding auxiliary data.

The invention yet further provides a method for increased data access performed by a receiver/computer in a packetswitched network, said receiver/computer including an operating unit, a first memory, a permanent storage memory, a processor and a network cache memory, said method comprising the steps of receiving a message containing a digital digest from said network; searching for data with the same digital digest in said network cache memory, and if data having the same digital digest as the digital digest received is not uncovered, forming a negative indication signal and transmitting it back through said network.

Still further, the invention provides a method for increased data access performed by a receiver/computer in a packet-switched network, said receiver/computer including an operating unit, a first memory, a permanent storage memory, a processor and a network cache memory, said method comprising the steps of receiving a message containing a digital digest from said network; searching for data with the same digital digest in said network cache memory, and if data having the same digital digest as the digital digest received is uncovered, forming a positive indication signal and transmitting it back through said network.

In addition, the invention provides a method for increased data access performed by a receiver/computer in a packetswitched network, said receiver/computer including an operating unit, a first memory, a permanent storage memory, a processor and a network cache memory, said method comprising the steps of receiving a message containing a principal digital digest and one or more auxiliary digital digests from said network; searching in predetermined locations in said permanent storage memory for data with a digital digest substantially identical to said principal digital digest; searching in predetermined locations in said permanent storage memory for data with a digital digest substantially identical to one of said auxiliary digital digests; and if data having the same digital digest as one of said auxiliary digital digests received is uncovered, forming a partial indication signal and transmitting it back through said network.

Yet further, the invention provides a method for increased The invention further provides a method performed by a 40 data access performed by a computer system in a packetswitched network, said computer system including a network cache memory and being operationally interposed between a sender/computer and a receiver/computer so that data packets sent between said sender/computer and said receiver/computer are delivered through said computer system; said method comprising the steps of intercepting a message containing a digital digest transmitted from said sender/computer to said receiver/computer, and transmitting data with a digital digest substantially identical to the digital or negative indication signal for said digital digest, and if a 50 digest received from said sender/computer to said receiver/ computer.

In addition, the invention provides a method for increased data access performed by a computer system in a packetswitched network, said computer system including a network cache memory and being operationally interposed between a sender/computer and a receiver/computer so that data packets sent between said sender/computer and said receiver/computer are delivered through said computer system; said method comprising the steps of intercepting a message containing a digital digest transmitted from said sender/computer to said receiver/computer; intercepting a message containing an indication signal other than a positive indication signal transmitted from said receiver/computer to said sender/computer in response to said message containing signal is received, said sender/computer transmitting a sig- 65 a digital digest, and transmitting data with a digital digest substantially identical to the digital digest received from said sender/computer to said receiver/computer.

US 6,757,717 B1

5

Additionally, the invention provides a method for increased data access performed by a client computer in a packet-switched network, said client computer including an operating unit, a first memory and a processor, said method comprising the steps of sending a request for data from said client computer to a server, said request containing digital digests for different data; said server preparing a response to said request, searching for data with a digital digest substantially identical to one of the digital digests received in said request, and producing the difference between said response and the uncovered data.

Finally, the invention provides apparatus for increased data access in a packet-switched network, comprising a computer connected to said packet-switched network, including an operating unit, a first memory, a permanent storage memory, a processor and a network cache memory; means for calculating digital digests of data in said network cache memory; means for comparison between digital digest, and means for sending the results of comparison between a digital digest received from another computer in said network and a digital digest calculated on data in said network. The operations

The invention will now be described in connection with certain preferred embodiments with reference to the following illustrative figures so that it may be more fully understood.

With specific reference now to the figures in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of the preferred embodiments of the present invention only, and are presented in the cause of providing what is believed to be the most useful and readily understood description of the principles and conceptual aspects of the invention. In this regard, no attempt is made to show structural details of the invention in more detail than is necessary for a fundamental understanding of the invention, the description taken with the drawings making apparent to those skilled in the art how the several forms of the invention may be embodied in practice.

BRIEF DESCRIPTION OF THE DRAWINGS

- FIG. 1 illustrates a prior art wide-area network;
- FIG. 2 illustrates a prior art wide-area network with a caching gateway;
- FIG. 3 is a flow diagram of the method of calculating the difference between two data digests according to the present invention:
- FIG. 4 is a block diagram of a first embodiment of a sender/computer-receiver/computer system according to the present invention;
- FIG. 5 is a schematic representation illustrating the interaction between a sender/computer and a receiver/computer according to the system of FIG. 4;
- FIG. 6 is a flow diagram illustrating the method of operating the sender/computer according to the present invention:
- FIG. 7 is a flow diagram illustrating the method of operating the receiver/computer according to the present invention;
- FIG. 8 is a schematic representation illustrating the interaction between a sender/computer and a receiver/computer 60 28. according to another embodiment of the present invention;
- FIG. 9 is a flow diagram illustrating the method of operating the sender/computer according to a further embodiment of the present invention;
- FIG. 10 is a flow diagram illustrating the method of 65 operating the receiver/computer according to the embodiment of FIG. 9;

FIG. 11 is a block diagram of the configuration of the gateway system according to the present invention;

FIG. 12 is a schematic representation of the interaction between a sender/computer, a receiver/computer, and the gateway configuration according to the present invention;

FIG. 13 is a flow diagram of the operation of the gateway;

FIG. 14 is a block diagram of a further configuration of a sender/computer-receiver/computer system according to the present invention; and

FIG. 15 is a schematic representation of the interaction between the sender/computer-receiver/computer system of FIG. 14.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The performance gains realized by the present invention are derived from the fact that computers in common widearea networks tend to repetitively transmit the same data over the network.

The operations described herein may take the form of electrical or optical signals. The packet-switched network may be Internet.

The term "digital digest" as used herein refers to the per se known MD5 algorithm, described in RFC 1321 by R. Rivest, which is a preferred calculation method. Other algorithms may, however, just as well be used. For example, a digital digest may be calculated according to the CRC algorithm, or by applying the CRC algorithm to different subsets or different reorderings of data, or by consecutively applying CRC and MD5. In addition, any other algorithm may be used, provided that it produces a fixed-size binary value calculated from arbitrarily-sized binary data in such a way that it depends only on the contents of said data and that the probability of two different data having the same digital digest, is low.

Whenever means for calculating the difference between two data are mentioned herein, the method as shown in FIG. 3 may be employed. The data are referred to as D1 and D2. The difference between them consists of three parts: the number of fragment pairs, the array of fragment pairs, and the remainder of D1. A fragment pair is a pair representing the distance from the beginning of this fragment to the end of the previous one, and the number of octets in the fragment (Dist_Length). A marker m1 is set at the beginning of the data D1 and a marker m2 at the beginning of D2.

An octet m1 is designated as *m1 and an octet m2 as *m2. An integer K>1, which represents a minimal length of a fragment encoded, e.g., K=3, is chosen.

As stated above, m1 is set at the beginning of D1, m2 at the beginning of D2, and Dist=0 is assigned at 14. A loop is then entered: if m1 is at the end of D1 (16), a number of fragment pairs is saved at 18, and the algorithm is completed. If m2 is at the end of D2 (20), the rest of D1 from m1 is saved at 22, a number of fragment pairs is saved, and the algorithm is completed. If *m1 equals *m2 (24), a subroutine "Fragment" is entered at 26; otherwise, m2 is moved by one octet toward the end of D2 and Dist is increased by 1 at 28.

The subroutine "Fragment" proceeds as follows: New markers t1=m1 and t2=m2 are set and Length=0 is assigned at 30. t1 and t2 are moved by an octet toward the ends of D1 and D2 and Length is increased at 32. If t1 is at the end of D1, or t2 is at the end of D2, or *t1 does not equal *t2 at the end of the fragment (34), then the Length is a length of the fragment and Dist is the distance between the beginning of

US 6,757,717 B1

7

this fragment and the end of the previous one. If the Length <K as determined by 36, the fragment is dropped at 38, m2 is moved by one octet and the subroutine is terminated. Otherwise, the pair (Dist, Length) is saved, the number of pairs is increased by one, m1 and m2 are moved by Length 5 octets toward the ends of D1 and D2, and Dist is reset to 0 at 40. The subroutine is ended.

The sequence of fragment pairs may be further reduced in size by using the per se known Huffman encoding or by using an arithmetic coding, e.g., as disclosed in U.S. Pat. No. 4,122,440.

Restoration of the data is simple. Marker m2 is set at the beginning of the known D2. Then for each fragment pair (Dist, Length) from the known difference, m2 is moved by Dist octets, Length octets are copied from m2 to D1 and m2 is moved by Length. Then the rest of D1 is copied from the remainder

An embodiment of a sender/computer-receiver/computer system according to the present invention is schematically illustrated in FIG. 4. A preferred embodiment is a network computer system having at least two computers. A sender/ 20 computer 42 (also referred to herein as "sender/computer") having an operating unit, a first memory, a permanent storage memory and a processor, is connected to the network by any network connection 44. A remote receiver/computer 46 (also referred to herein as "receiver/computer") having an 25 operating unit, a first memory, a permanent storage memory and a processor, is also connected to the network. The receiver/computer 46 uses a part of its permanent storage memory or its first memory, or both, as network cache memory 48. The sender/computer has calculation means 50 30 for calculating a digital digest on data in its first memory or in its permanent storage memory. Similarly, the receiver/ computer has calculating means 52 for calculating a digital digest on data stored in its network cache memory 48. The receiver/computer also has comparison means 54 for comparing between such a calculated digital digest and a digital digest received from the network.

An example of a first memory could be a RAM; an example of a permanent storage memory may be a disk drive, a flash RAM or a bubble memory.

It is possible to modify this system in different ways. The receiver/computer 46 and sender/computer 42 may each include means for storing the calculated digital digest in its first memory or permanent storage memory. Additionally, the receiver/computer 46 may have means for calculating a digital digest on data in its permanent storage memory outside of its cache memory. Furthermore, the system may be modified in such a way that the sender/computer 42 has means 56 for calculating the difference between two data objects.

Interaction between the receiver/computer and the sender/ computer is depicted in FIGS. 5 to 7. The data sender/ computer 42 calculates a digital digest on the data in means 50 and then transmits the calculated digest to receiver/ computer 46. The receiver/computer receives the digital 55 digest from sender/computer 42 and then searches its network cache memory 48 for data with the same digest. If it finds such data, it uses it as if it were received from the sender/computer 42 and issues a positive indication signal to the sender/computer. Otherwise, it sends a negative indica- 60 tion signal to the sender/computer. Upon receiving a negative indication signal, the sender/computer transmits the data. Upon receiving a positive indication signal, or upon expiration of a predefined period of time, the sender/ computer completes the transaction. This transaction begins 65 with a receiver/computer sending a request to the sender/ computer.

8

The above-described method may be modified in different ways. For example, absence of a signal from the receiver/computer for a predetermined period of time may be considered by the sender/computer to be a negative indication signal. Alternatively, the digital digests for some data may be stored in the permanent storage memory of the sender/computer and obtained from there, or a plurality of data may be processed in one transaction, a digital digest being calculated for each data object and a separate indication signal issued on each digital digest.

Another method of interaction between the receiver/ computer 46 and the sender/computer 42 is illustrated in FIGS. 8-10. The data sender/computer calculates a digital digest on the data to be sent (hereinafter, "principal digest") and for one or more other data objects (hereinafter, "auxiliary digests"). Without limiting the scope of the invention, the following data objects may be recommended: (a) a previous version of the data requested; (b) a file similar to the data requested. Then the sender/computer sends the principal and auxiliary digests to the receiver/computer. Upon receiving a message with these digital digests from the sender/computer, the receiver/computer searches its network cache memory 48 for data having the principal digest. If such data is found, it uses it as if it were received from sender/computer 42 and issues a positive indication signal to the sender/computer. Otherwise, receiver/computer 46 searches its network cache memory 48 for data with the auxiliary digests. If it finds data with a digital digest substantially equal to one of the auxiliary digests, it issues a partial indication signal to the sender/computer, with a reference to the digest. Otherwise, it issues a negative indication signal to the sender/computer. Upon receiving a negative indication signal, the sender/computer sends the data. Upon receiving a partial indication signal, the sender/ computer transmits the difference between the digital digest of the data required to be sent and that of the data whose digital digest was found by the receiver/computer. This transaction may also begin with the receiver/computer sending a request to the sender/computer.

A modification of the above method is possible. For example, absence of the indication signal from the receiver/ computer for a predefined period of time may be considered by the sender/computer as a negative indication signal, or the digital digests for some data may be stored in the permanent storage memory of the sender/computer and obtained from there instead of being calculated immediately before the transaction. Alternatively, a plurality of data may be processed in one transaction; a digital digest is calculated for each data object and a separate indication signal issued on every digital digest. Still alternatively, receiver/computer 46 may search not only in its network cache memory 48, but also in predefined locations in its permanent storage memory. Sender/computer 42 may add to a digest it sends to the receiver/computer information about the possible location of the data with that digital digest in the receiver/ computer's permanent storage memory.

Another embodiment of the present invention is schematically illustrated in FIG. 11. Shown is a system comprising a gateway computer or gateway 60 including an operating unit, a first memory and a processor, and a caching computer 62 including an operating unit, a first memory, a permanent storage memory and a processor, connected to the gateway 60 through any fast network connection 64, e.g., Ethernet. Gateway 60 is connected to a wide-area packet-switched network in such a way that network packets sent between at least two other computers 42 and 46 pass through the gateway 60. The caching computer 62 uses a part of its

permanent storage memory for network cache memory 66. Caching computer 62 has means 68 for calculating the digital digest of data in its network cache memory 66, and means 70 for comparison between such a calculated digital digest and a digital digest received by gateway computer 60 from the wide-area network. It should be noted that gateway computer 60 may be integrally formed with the caching computer. The caching computer may have means for storing a calculated digital digest in its first memory or permanent storage memory.

By way of example, operations which may be performed in such a system will now be described with reference to FIGS. 12 and 13. The gateway 60, operationally interposed between a sender/computer 42 and a receiver/computer 46, intercepts a digital digest sent from the sender/computer to the receiver/computer, saves it in its memory, and passes it 15 unchanged to the receiver/computer 46. Then the gateway 60 intercepts an indication signal other than a positive indication signal issued by the receiver/computer. If there was a digest for this indication signal, the caching computer 62 searches for data with the same digital digest in its 20 network cache memory 66. If that digest is found, then the gateway sends the data to the receiver/computer, changes the indication signal to positive, and then passes the indication signal to sender/computer 42.

Further, the caching computer 62 may verify a digital 25 digest for a data object stored in its network cache memory 66 by calculating the digital digest for that data and comparing it to the digest stored in the network cache memory. The calculated digital digest may be stored in the network cache memory 66 and the data object-digital digest pair may 30 be marked as not requiring further verification.

Another further embodiment of the present invention is schematically illustrated in FIG. 14. It consists of a network computer system comprising at least two computers: a sender/computer 42 including an operating unit, a first 35 memory, a permanent storage memory and a processor which is connected to a network 44. A remote receiver/ computer 46 having an operating unit, a first memory, a permanent storage memory and a processor is also connected to the network. The receiver/computer uses a part of 40 its permanent storage memory or its first memory, or both, for network cache memory 72. The sender/computer 42 has means 74 for calculating a digital digest for data in its memory or in its permanent storage. The receiver/computer 46 has means 76 for calculating a digital digest for data 45 stored in its network cache memory. The sender/computer 42 also has means 78 for comparison between such a calculated digital digest and a digital digest received from the network. The sender/computer further includes means 80 receiver/computer 46 includes means 82 for restoring a data object from another data object and the difference between said data object being restored and said another data object.

An interaction between the sender/computer and receiver/ computer according to this system is illustrated in FIG. 15. 55 When receiver/computer 46 is required to request data from the server or sender/computer 42, it calculates one or more digital digests for different data objects stored in its network cache memory 72 or in its permanent storage memory. Without limiting the scope of the invention, the following 60 data objects may be recommended: (a) a previous version of the data requested; (b) a file similar to the data requested; (c) a data set similar to the data requested, which may be generated in a first memory; (d) a large data file or database including fragments of octets, similar to the data requested. 65 comprising:

The receiver/computer then transmits a request for data, containing one or more of the above-mentioned digital digests. The sender/computer prepares a response to the request, and then calculates a digital digest on the data in the response. If the calculated digest is equal to one of the digital digests in the request, the sender/computer sends a confirmation. Otherwise, the sender/computer may continue searching for the data objects with the same digital digests in the predefined subset of its permanent storage memory. If it finds such data, it calculates the difference between this data and the data in the response, and sends only the

response as prepared.

Variations of the above method are envisioned. For example, a number of requests for data may be sent simultaneously. The digital digests on the receiver/computer may be calculated earlier and stored in the permanent memory of the receiver/computer. The digital digests on the sender/ computer may also be calculated earlier and stored in the permanent memory of the sender/computer.

difference. Otherwise, the sender/computer sends the

It will be evident to those skilled in the art that the invention is not limited to the details of the foregoing illustrated embodiments and that the present invention may be embodied in other specific forms without departing from the spirit or essential attributes thereof. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

What is claimed is:

- 1. A system for data access in a packet-switched network, comprising:
 - a sender/computer including an operating unit, a first memory, a permanent storage memory and a processor and a remote receiver/computer including an operating unit, a first memory, a permanent storage memory and a processor, said sender/computer and said receiver/ computer communicating through said network;
 - said sender/computer further including means for creating digital digests on data;
 - said receiver/computer further including a network cache memory and means for creating digital digests on data in said network cache memory; and
 - said receiver/computer including means for comparison between digital digests.
- 2. The system as claimed in claim 1, wherein said receiver/computer further includes means for a digital digest for data stored in said permanent storage memory.
- 3. The system as claimed in claim 1, wherein said for calculating the difference between two data objects, and 50 receiver/computer further includes means for storing said created digital digest in its first or permanent memory.
 - 4. The system as claimed in claim 1, wherein said sender/computer further includes means for the difference between two data objects and said receiver/computer further includes means for restoring a data object from another data object and the difference between said data object being restored and said another data object.
 - 5. The system as claimed in claim 1, wherein said sender/computer further includes means for the difference between two data objects and said receiver/computer further includes means for restoring a data object from another data object and the difference between said data object being restored and said another data object.
 - A system for data access in a packet-switched network,
 - a gateway including an operating unit, a memory and a processor connected to said packet-switched network

10

in such a way that network packets sent between at least two other computers pass through it;

a caching computer connected to said gateway through a fast local network, wherein said caching computer includes an operating unit, a first memory, a permanent s storage memory and a processor;

said caching computer further including a network cache memory in its permanent storage memory, means for a digital digest and means for comparison between a digital digest on data in its network cache memory and 10 a digital digest received from said packet-switched network through said gateway.

7. The system as claimed in claim 6, wherein said caching computer further includes means for a digital digest for data in its network cache memory.

8. The system as claimed in claim 6, wherein said caching 15 computer is integrally formed with said gateway.

9. The system as claimed in claim 6, wherein said caching computer further includes means for storing said digital digest in said permanent storage memory.

10. A system for data access in a packet-switched 20 network, comprising:

a sender/computer including an operating unit, a first memory, a permanent storage memory and a processor and a remote receiver/computer including an operating unit, a first memory, a permanent storage memory and 25 a processor, said sender/computer and said receiver/ computer communicating through a network;

said sender/computer further including means for creating digital digests on data, and

said receiver/computer further including a network cache 30 memory, means for storing a digital digest received from said network in its permanent storage memory and means for comparison between digital digests.

11. A method performed by a sender/computer in a packet-switched network for increasing data access, said 35 of: sender/computer including an operating unit, a first memory, a permanent storage memory and a processor and said sender/computer being operative to transmit data to a receiver/computer, the method comprising the steps of:

creating and transmitting a digital digest of said data from 40 said sender/computer to said receiver/computer;

receiving a response signal from said receiver/computer at said sender/computer, said response signal containing a positive, partial or negative indication signal for said digital digest, and

if a negative indication signal is received, transmitting said data from said sender/computer to said receiver/

12. The method as claimed in claim 11, wherein said sender/computer creates said digital digest for the data 50 before transmitting it to said receiver/computer.

13. The method as claimed in claim 12, wherein said sender/computer transmits the data to said receiver/ computer after a preset period of time has passed since transmitting said digital digest to said receiver/computer and 55 receiver/computer in a packet-switched network, said a response signal has not been received.

14. The method as claimed in claim 12, wherein, when a plurality of data objects is to be sent, a digital digest is sent for each of said data objects and a response signal is sent containing a separate indication signal for each of said data 60 objects.

15. The method as claimed in claim 12, wherein said digital digest creation comprises the step of Cyclic Redundancy Check against the contents of the data.

16. The method as claimed in claim 12, wherein said 65 digital digest creation comprises the step of MD5 against the contents of the data.

12

17. A method for increasing data access performed by a sender/computer in a packet-switched network, said sender/ computer including an operating unit, a first memory, a permanent storage memory and a processor and said sender/ computer being operative to transmit principal data to a receiver/computer, said method comprising the steps of:

creating and transmitting digital digests of said principal data and of one or more auxiliary data from said sender/computer to said receiver/computer;

receiving a response signal at said sender/computer from said receiver/computer, said response signal containing a positive, negative or partial indication signal, and

if a partial indication signal is received, said sender/ computer transmitting a signal constituting the difference between said principal data and corresponding auxiliary data.

18. The method as claimed in claim 17, wherein additional information about the probable location of auxiliary data in said permanent storage memory of the receiver/ computer is encoded and transmitted together with the corresponding digital digest.

19. The method as claimed in claim 17, wherein said sender/computer creates said digital digest for data before transmitting said digital digest to said receiver/computer.

20. The method as claimed in claim 17, wherein said digital digest is obtained from the permanent storage memory of said sender/computer.

21. The method as claimed in claim 17, wherein said digital digest creation comprises the step of Cyclic Redundancy Check against the contents of the data.

22. A method for increased data access performed by a receiver/computer in a packet-switched network, said receiver/computer including an operating unit, a first memory, a permanent storage memory, a processor and a network cache memory, said method comprising the steps

receiving a message containing a digital digest from said network;

searching for data with the same digital digest in said network cache memory,

if data having the same digital digest as the digital digest received is not uncovered, forming a negative indication signal and transmitting it back through said network: and

creating a digital digest for data received from said network cache memory.

23. The method as claimed in claim 22, further comprising searching in predetermined locations in said permanent storage memory for data with a digital digest substantially identical to the digital digest received from said network.

24. The method as claimed in claim 22, wherein a plurality of digital digests for different data objects is received in the same message and an indication signal is generated separately for each of said data objects.

25. A method for increased data access performed by a receiver/computer including an operating unit, a first memory, a permanent storage memory, a processor and a network cache memory, said method comprising the steps

receiving a message containing a principal digital digest and one or more auxiliary digital digests from said network, wherein said auxiliary digital digests are correlated to data objects similar to the data object represented by said principal digest;

searching in predetermined locations in said permanent storage memory for data with a digital digest substantially identical to said principal digital digest;

US 6,757,717 B1

13

- searching in predetermined locations in said permanent storage memory for data with a digital digest substantially identical to one of said auxiliary digital digests; and
- if data having the same digital digest as one of said 5 auxiliary digital digests received is uncovered, forming a partial indication signal and transmitting it back through said network.
- 26. The method as claimed in claim 25, further comprising the step of searching the network cache memory for data with said principal digital digest.
- 27. The method as claimed in claim 26, further comprising the step of searching in said network cache memory for data with one of said auxiliary digital digests.
- 28. A method for increased data access performed by a computer system in a packet-switched network, said computer system including a network cache memory and being operationally interposed between a sender/computer and receiver/computer so that data packets sent between said sender/computer and said receiver/computer are delivered through said computer system; said method comprising the steps of:
 - intercepting a message containing a digital digest transmitted from said sender/computer to said receiver/ computer, and
 - transmitting data with a digital digest substantially identical to the digital digest received from said sender/computer to said receiver/computer in response to said message, whereby said sender/computer is relieved of the burden of transmitting said data.
- 29. The method of claim 28 further comprising the step of receiving said data into the network cache memory prior to intercepting the message.
- 30. A method for increased data access performed by a computer system in a packet-switched network, said computer system including a network cache memory and being operationally interposed between a sender/computer and a receiver/computer so that data packets sent between said sender/computer and said receiver/computer are delivered through said computer system; said method comprising the steps of:

14

- intercepting a message containing a digital digest transmitted from said sender/computer to said receiver/ computer:
- intercepting a message containing an indication signal other than a positive indication signal transmitted from said receiver/computer to said sender/computer in response to said message containing a digital digest, and
- transmitting data with a digital digest substantially identical to the digital digest received from said sender/computer to said receiver/computer, whereby said sender/computer is relieved of the burden of transmitting said data.
- 31. The method of claim 30 further comprising the step of receiving said data into the network cache memory prior to intercepting the message.
- 32. A method for increased data access performed by a client computer in a packet-switched network, said client computer including an operating unit, a first memory and a processor, said method comprising the steps of:
 - sending a request for a single first data object from said client computer to a server, said request containing multiple digital digests for different data objects similar to said first data object;
 - said server preparing a response to said request, searching for a second data object with a digital digest substantially identical to one of the digital digests received in said request, and producing the difference between said first data object and the uncovered second data object.
- 33. The method as claimed in claim 32, further comprising the step of transmitting said difference to said client computer.
- 34. The method as claimed in claim 33, further comprising the step of using said difference for restoring the data from said response in said client computer.

* * * * *

UNITED STATES DISTRICT COURT CENTRAL DISTRICT OF CALIFORNIA

NOTICE OF ASSIGNMENT TO UNITED STATES MAGISTRATE JUDGE FOR DISCOVERY

This case has been assigned to District Judge Cormac J. Carney	and the assigned
discovery Magistrate Judge is Arthur Nakazato.	

The case number on all documents filed with the Court should read as follows:

SACV11- 1684 CJC (ANx)

Pursuant to General Order 05-07 of the United States District Court for the Central District of California, the Magistrate Judge has been designated to hear discovery related motions.

All discovery related motions should be noticed on the calendar of the Magistrate Judge				
NOTICE TO COUNSEL				

A copy of this notice must be served with the summons and complaint on all defendants (if a removal action is

[X] Southern Division

Failure to file at the proper location will result in your documents being returned to you.

filed, a copy of this notice must be served on all plaintiffs).

Subsequent documents must be filed at the following location:

[] Western Division

312 N. Spring St., Rm. G-8

Los Angeles, CA 90012

411 West Fourth St., Rm. 1-053

Santa Ana, CA 92701-4516

[] Eastern Division

3470 Twelfth St., Rm. 134

Riverside, CA 92501

UNITED STATES DISTRICT COURT

for the

Central District of California

Proxyconn, Inc.)	
Plaintiff)	SACV11 01604 CIG (12)
v. Acer America Corporation) Civil Action No.)	SACV11-01684 CJC (ANx)
Defendant)	

SUMMONS IN A CIVIL ACTION

To: (Defendant's name and address) Acer America Corporation

A lawsuit has been filed against you.

Within 21 days after service of this summons on you (not counting the day you received it) — or 60 days if you are the United States or a United States agency, or an officer or employee of the United States described in Fed. R. Civ. P. 12 (a)(2) or (3) — you must serve on the plaintiff an answer to the attached complaint or a motion under Rule 12 of the Federal Rules of Civil Procedure. The answer or motion must be served on the plaintiff or plaintiff's attorney,

whose name and address are:

Marc A. Fenster RUSS AUGUST & KABAT

12424 Wilshire Boulevard, 12th Floor

Los Angeles, CA 90025 Tel: (310) 826-7474

If you fail to respond, judgment by default will be entered against you for the relief demanded in the complaint. You also must file your answer or motion with the court.

Date:	NOV = 3 2011	ROLLS ROYCE PASCHAL
	***************************************	Signature of Clerk or Deputy Clerk



AO 440 (Rev. 12/09) Summons in a Civil Action (Page 2)

Civil Action No.

PROOF OF SERVICE

(This section should not be filed with the court unless required by Fed. R. Civ. P. 4 (1))

	This summons for (nan	ne of individual and title, if any)		
as re	ceived by me on (date)	•		
	☐ I personally served	the summons on the individual	at (place)	
			on (date)	; or
	☐ I left the summons:	at the individual's residence or a	usual place of abode with (name)	
			of suitable age and discretion who resi	des there,
	on (date)	***************************************	the individual's last known address; or	
	☐ I served the summo	ns on (name of individual)		, who is
	designated by law to a	ccept service of process on beha	alf of (name of organization)	***************************************
			on (date)	; or
	☐ I returned the summ	nons unexecuted because		; or
	☐ Other (specify):	Malari Adminis	ta et antakkinggah didukkingan gibidag pikala (sirang kinang Kal) a dakambi ang menggap (APA) daga 1 st. at sacabaliski mulain at	kildedekkisterkildedekist (Azarokista) yarildari Azarokiste yarildakilda
	My fees are \$	for travel and \$	for services, for a total of \$	0.00
	I declare under penalty	of perjury that this information	is true.	
. 4				
ate:	***************************************	***************************************	Server's signature	A
			Printed name and title	ra meroni kraniku krani anunu masuusu asuusu asuu asuu asuu asuu asu
				**
,				
			Server's address	

Additional information regarding attempted service, etc:

UNITED STATES DISTRICT COURT, CENTRAL DISTRICT OF CALIFORNIA CIVIL COVER SHEET

CIVIL COVER SHEET							
I (a) PLAINTIFFS (Check box Proxyconn, Inc.	if you are representing yourself □)		DEFENDANTS Acer America Corporation	on			
(b) Attorneys (Firm Name, Adyourself, provide same.)	dress and Telephone Number. If you are	representing	Attorneys (If Known)				
Marc A. Fenster, RUSS Al Los Angeles, CA 90025,	UGUST & KABAT, 12424 Wilshire Blv Tel (310) 826-7474	vd., 12th Fl.					
II. BASIS OF JURISDICTION	N (Place an X in one box only.)		HIP OF PRINCIPAL PAR		y Cases Only	· · · · · · · · · · · · · · · · · · ·	
□ 1 U.S. Government Plaintiff	63 Federal Question (U.S. Government Not a Party)	Citizen of This S				PTF DEF □4 □4	
☐ 2 U.S. Government Defendant	☐ 4 Diversity (Indicate Citizenship of Parties in Item III)	Citizen of Anoth	ner State		ted and Principal Place ss in Another State	5 5	
		Citizen or Subje	ct of a Foreign Country 🔲	3 □3 Foreign N	ation	□6 □6	
IV. ORIGIN (Place an X in one	e box only.)						
19 1 Original 2 Remove Proceeding State Co	+ 4, +	einstated or D 5 eopened	Transferred from another d	listrict (specify):	District Judg	eal to District e from istrate Judge	
	AINT: JURY DEMAND: DY Yes	No (Check 'Yes	only if demanded in compli	aint.)			
CLASS ACTION under F.R.C.	.P. 23: □ Yes 👿 No		MONEY DEMANDED IN	COMPLAINT: \$			
VI. CAUSE OF ACTION (Cite Patent Infringment	the U.S. Civil Statute under which you	are filing and wri	te a brief statement of cause.	Do not cite jurisdicti	onal statutes unless dive	ersity.)	
VII. NATURE OF SUIT (Place	e an X in one box only.)						
		TORTS RSONAL INJURY Airplane	TORTS PERSONAL PROPERTY	PRISONER PETITIONS D 510 Motions to	3 □ 710 Fair Lal	COLUMN BOLL SAN PRODUCE	
☐ 430 Banks and Banking ☐ 450 Commerce/ICC	☐ 130 Miller Act ☐ 315 ☐ 140 Negotiable Instrument	Airplane Produc Liability Assault, Libel &	t □ 370 Other Fraud □ 371 Truth in Lendin	Vacate Ser g Habeas Co □ 530 General		is	
☐ 460 Deportation ☐ 470 Racketeer Influenced and Corrupt	Overpayment & Enforcement of Indement	Slander Fed. Employers' Liability	Property Damag	ge □ 535 Death Penage □ 540 Mandamus	alty Reporti	ng & ure Act	
Organizations	☐ 151 Medicare Act ☐ 152 Recovery of Defaulted ☐ 345	Marine Marine Product Liability	BANKRUPTCY 422 Appeal 28 USC 158		ts □ 790 Other L adition Litigation	abor on	
☐ 810 Selective Service ☐ 850 Securities/Commodities/	Veterans) □ 153 Recovery of	Motor Vehicle Motor Vehicle Product Liability	☐ 423 Withdrawal 28	PENALTY	Security PROPERTY	Act RIGHTS	
	Veteran's Benefits ☐ 160 Stockholders' Suits ☐ 362	Other Personal Injury Personal Injury-	☐ 441 Voting ☐ 442 Employment	Drug □ 625 Drug Relat	830 Patent □ 840 Tradem	ark	
☐ 890 Other Statutory Actions ☐ 891 Agricultural Act ☐ 892 Economic Stabilization	☐ 190 Other Contract ☐ 195 Contract Product ☐ 365 ☐ Liability	Med Malpractice Personal Injury- Product Liability	mmodations	Seizure of Property 2 881		•	
Act ☐ 893 Environmental Matters	□ 196 Franchise □ 368 REAL PROPERTY	Asbestos Person Injury Product	al 445 American with Disabilities -	☐ 630 Liquor Lav	ick (405(g)))	
☐ 895 Freedom of Info. Act ☐ 900 Appeal of Fee Determination Under Equal	☐ 230 Rent Lease & Ejectment ☐ 462 ☐ 240 Torts to Land	Liability MMIGRATION Naturalization Application	Employment American with Disabilities - Other	☐ 650 Airline Re ☐ 660 Occupation Safety /He ☐ 690 Other	nal ☐ 865 RSI (40 alth ☐ FEDERAL T ☐ 870 Taxes (1	5(g)) AX SUITS U.S. Plaintiff	
Access to Justice ☐ 950 Constitutionality of State Statutes	☐ 245 Tort Product Liability ☐ 290 All Other Real Property ☐ 465	Habcas Corpus- Alien Detainee Other Immigrati Actions	☐ 440 Other Civil Rights		or Defe □ 871 IRS-Thi USC 76	rd Party 26	
	40				<u> </u>		
	C A 77874 A	1604 616	' (A NTwr)				
FOR OFFICE USE ONLY:	FOR OFFICE USE ONLY: Case Number: SACV11-01684 CJC (ANX)						

AFTER COMPLETING THE FRONT SIDE OF FORM CV-71, COMPLETE THE INFORMATION REQUESTED BELOW.

.

CV-71 (05/08)

UNITED STATES DISTRICT COURT, CENTRAL DISTRICT OF CALIFORNIA CIVIL COVER SHEET

VIII(a). IDENTICAL CASES: Has If yes, list case number(s):	this action been pre	viously filed in this court an	d dismissed, remanded or closed? ■ No □ Yes			
VIII(b). RELATED CASES: Have If yes, list case number(s):	any cases been prev	viously filed in this court that	t are related to the present case? ™No □ Yes			
□ B. (□ C. 1	Arise from the same Call for determination For other reasons we	or closely related transaction on of the same or substantiall ould entail substantial duplica	ns, happenings, or events; or ly related or similar questions of law and fact; or ation of labor if heard by different judges; or <u>and</u> one of the factors identified above in a, b or c also is present.			
IX. VENUE: (When completing the						
a) List the County in this District; California County outside of this District; State if other than California; or Foreign Country, in which EACH named plaintiff resides. Check here if the government, its agencies or employees is a named plaintiff. If this box is checked, go to item (b).						
County in this District:*			California County outside of this District; State, if other than California; or Foreign Country			
Orange County						
(b) List the County in this District; □ Check here if the government, it	California County or is agencies or emplo	utside of this District; State it	f other than California; or Foreign Country, in which EACH named defendant resides. If this box is checked, go to item (c).			
County in this District:*			California County outside of this District; State, if other than California; or Foreign Country			
			Santa Clara County			
(c) List the County in this District; Note: In land condemnation c:	California County or	utside of this District; State i	f other than California; or Foreign Country, in which EACH claim arose.			
County in this District:*			California County outside of this District; State, if other than California; or Foreign Country			
Urange County						
* Los Angeles, Orange, San Bernai	dine, Riverside, Ve	entura, Santa Barbara, or S	San Luis Obispo Counties			
Note: In land condemnation cases, use the location of the tract of land involved X. SIGNATURE OF ATTORNEY (OR PRO PER): March C. Lender Date November 2, 2011						
Notice to Counsel/Parties: The or other papers as required by lay	ne CV-71 (JS-44) Ci	ivil Cover Sheet and the infor	rmation contained herein neither replace nor supplement the filing and service of pleadings see of the United States in September 1974, is required pursuant to Local Rule 3-1 is not filed ting the civil docket sheet. (For more detailed instructions, see separate instructions sheet.)			
Key to Statistical codes relating to So	ocial Security Cases:					
Nature of Suit Code	Abbreviation	Substantive Statement of	f Cause of Action			
861	НІА	All claims for health insurance benefits (Medicare) under Title 18, Part A, of the Social Security Act, as amended. Also, include claims by hospitals, skilled nursing facilities, etc., for certification as providers of services under the program. (42 U.S.C. 1935FF(b))				
862	BL	All claims for "Black Lung" benefits under Title 4, Part B, of the Federal Coal Mine Health and Safety Act of 1969. (30 U.S.C. 923)				
863	DIWC	All claims filed by insured workers for disability insurance benefits under Title 2 of the Social Security Act, as amended; plus all claims filed for child's insurance benefits based on disability. (42 U.S.C. 405(g))				
863	DIWW	All claims filed for widows or widowers insurance benefits based on disability under Title 2 of the Social Security Act, as amended. (42 U.S.C. 405(g))				
864	SSID	All claims for supplement Act, as amended.	tal security income payments based upon disability filed under Title 16 of the Social Security			
865	RSI All claims for retirement (old age) and survivors benefits under Title 2 of the Social Security Act, as amended. (42 U.S.C. (g))					

CV-71 (05/08) CIVIL COVER SHEET Page 2 of 2